

SIMOTICS SD - 250 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	55.00	-/-	100.00	1480	355.0	93.5	93.9	93.5	0.85	0.81	0.72	6.8	2.7	3.0	IE2
690	Y	50	55.00	-/-	58.00	1480	355.0	93.5	93.9	93.5	0.85	0.81	0.72	6.8	2.7	3.0	IE2
460	Δ	60	63.00	-/-	99.00	1780	340.0	94.1	94.4	94.0	0.85	0.82	0.74	6.6	2.8	2.9	IE2
460	Δ	60	55.00	-/-	87.00	1785	295.0	94.1	94.1	93.3	0.84	0.80	0.71	7.3	3.1	3.3	IE2
IM B3 / IM 1001			FS 250 M		385 kg		IP55	IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 19.9 s | 34.1 s

Sound level (SPL / SWL) at 50Hz 60Hz	66.0 / 79.0 dB(A) ²⁾	69.0 / 83.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.7500 kg m²		Vibration severity grade	A
Bearing DE NDE	6315 C3	6315 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} , F _{Rad,min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	25 g 8000 h	25 g	Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish, resistant to salt-laden air C4
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(F) 1 temperature sensor KTY84-130 (2 terminals)
Type of bearing	Locating bearing DE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box position	top	Max. cross-sectional area	120.0 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	34.0 mm - 42.0 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	title 1LE1601-2CB23-4AF4-Z		document status released		customer	
				document number			
© Siemens AG 2021	L51+Q01+S03			rev. 01	creation date 2021-04-23 15:29	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2252B

SIMOTICS SD - 250 M - IM B3 - 4p

Special design

L51	Bearing insulation NDE	S03	Special paint finish in sea air resistant C4
Q01	Measuring nipple for SPM shock pulse measurement to monitor bearings		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released		customer			
	title 1LE1601-2CB23-4AF4-Z	document number					
© Siemens AG 2021	L51+Q01+S03	rev. 01	creation date 2021-04-23 15:29	language en	Page 2/2		