

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2280C

SIMOTICS SD - 280 S - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
400	Δ	50	45.00	-/-	83.00	985	435.0	92.7	93.4	93.2	0.84	0.81	0.72	6.3	2.7	2.6	IE2
690	Y	50	45.00	-/-	48.50	985	435.0	92.7	93.4	93.2	0.84	0.81	0.72	6.3	2.7	2.6	IE2
460	Δ	60	54.00	-/-	87.00	1185	435.0	92.1	92.7	92.5	0.85	0.82	0.75	6.4	2.5	2.5	IE1
460	Δ	60	45.00	-/-	72.00	1188	360.0	93.6	93.8	93.1	0.84	0.80	0.70	7.4	3.1	3.0	IE2
IM B3 / IM 1001		FS 280 S		460 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 16 s | 25.5 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	65.0 / 79.0 dB(A) ²⁾	67.0 / 81.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	1.1000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6317 C3	6317 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	30 g 30 g 8000 h		Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish, resistant to salt-laden air C4
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(F) 1 temperature sensor KTY84-130 (2 terminals)
Type of bearing	Locating bearing DE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	120.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34.0 mm - 42.0 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10	Cable gland	2 glands, 2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_K/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1601-2DC03-4AF4-Z D22+D47+L51+Q01+R16+S03			document number				
© Siemens AG 2021				rev. 01	creation date 2021-04-23 16:30	language en	Page 1/2	

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2280C

SIMOTICS SD - 280 S - IM B3 - 6p

Special design

D22	motor without CE character for export outside the EEA (see EU regulation 640/2009)	Q01	Measuring nipple for SPM shock pulse measurement to monitor bearings
D47	TR CU product safety certificate EAC for the Eurasian Customs Union	R16	EMC cable gland, maximum number
L51	Bearing insulation NDE	S03	Special paint finish in sea air resistant C4

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1601-2DC03-4AF4-Z			document number				
© Siemens AG 2021	D22+D47+L51+Q01+R16+S03			rev. 01	creation date 2021-04-23 16:30	language en	Page 2/2	