

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3130B

SIMOTICS SD - 132 S - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	5.50	-/-	18.80	1470	35.5	89.6	90.0	89.4	0.82	0.77	0.67	8.5	2.9	3.7	IE3
400	Y	50	5.50	-/-	10.80	1470	35.5	89.6	90.0	89.4	0.82	0.77	0.67	8.5	2.9	3.7	IE3
460	Y	60	6.30	-/-	10.40	1770	34.0	91.7	92.0	91.3	0.83	0.79	0.69	8.7	2.7	3.7	IE3
460	Y	60	5.50	-/-	9.30	1775	29.5	91.7	91.6	90.5	0.81	0.76	0.65	10.0	3.1	4.2	IE3
IM B5 / IM 3001			FS 132 S			IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 22 s 28.1 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	69 / 73 dB(A) ²⁾	69 / 73 dB(A) ²⁾	Vibration severity grade	A	
Moment of inertia	0.0340 kg m ²		Thermal class	F	
Bearing DE NDE	6308 2Z C3	6308 2Z C3	Duty type	S1	
bearing lifetime			Direction of rotation	bidirectional	
L _{10mh} F _{Rad} min 50 60Hz ¹⁾	for coupling operation	40000 h	32000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	74 kg	
Regreasing device	No		Coating (paint finish)	Special paint finish C3	
Grease nipple	-/-		Color, paint shade	RAL7030	
Type of bearing	Preloaded bearing DE		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)	
Condensate drainage holes	Yes (standard)		Method of cooling	IC416 - separately ventilated, surface cooled	
External earthing terminal	No				

Terminal box

Terminal box position	top	Max. cross-sectional area	6 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 H01	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	3 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _K /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1603-1CB02-2FB4-Z						
	F70+G12+M01			rev.	creation date	language	Page
© Siemens AG 2022				01	2022-02-14	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3130B

SIMOTICS SD - 132 S - IM B5 - 4p

Special design

F70	Mounting of separately driven fan	M01	Connection when shipped, star connection
G12	Rotary pulse encoder Sendix 5020 (TTL)		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE1603-1CB02-2FB4-Z F70+G12+M01			document number			
© Siemens AG 2022				rev. 01	creation date 2022-02-14	language en	Page 2/2