

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3164A

SIMOTICS SD - 160 L - IM B35 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	18.50	-/-	32.00	2955	60.0	92.4	92.8	92.4	0.90	0.87	0.80	9.0	2.8	4.2	IE3
690	Y	50	18.50	-/-	18.60	2955	60.0	92.4	92.8	92.4	0.90	0.87	0.80	9.0	2.8	4.2	IE3
460	Δ	60	21.30	-/-	32.00	3555	57.0	91.7	91.5	90.3	0.91	0.88	0.80	9.0	2.6	4.2	IE3
460	Δ	60	18.50	-/-	28.50	3560	49.5	91.7	91.5	90.3	0.89	0.86	0.78	10.2	3.0	4.8	IE3
IM B35 / IM 2001		FS 160 L				IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 13.5 s | 19.9 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	70 / 82 dB(A) ^{2) 3)}	77 / 89 dB(A) ^{2) 3)}	External earthing terminal	No
Moment of inertia	0.0680 kg m ²		Vibration severity grade	A
Bearing DE NDE	6309 Z C3	6309 Z C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
50 60Hz			Frame material	cast iron
Relubrication interval/quantity DE NDE	10 g 10 g	8000 h	Net weight of the motor (IM B3)	127 kg
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish C3
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M8x1 DIN 71412		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Type of bearing	Locating bearing DE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_B/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type	datasheet			document status	released	
	title	1LE1603-1DA43-4JB4-Z			document number		
© Siemens AG 2022		H01+L20			rev.	creation date	language
					929	2022-11-24	en
							Page
							1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3164A

SIMOTICS SD - 160 L - IM B35 - 2p

Special design

H01 Bolted on mounting feet (instead of cast) L20 Locating bearing, DE

Notes:

responsible dep.
DI MC LVM

technical reference

created by
DT Configurator

approved by

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

[Link documents](#)

SIEMENS

document type
datasheet

title
1LE1603-1DA43-4JB4-Z
H01+L20

document status
released

document number

