

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3164B

SIMOTICS SD - 160 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_l/I_N	T_l/T_N	T_B/T_N	
500	Δ	50	15.00	-/-	23.00	1475	97.0	92.1	92.3	91.5	0.82	0.76	0.65	8.5	2.5	3.8	IE3
575	Δ	60	17.30	-/-	22.50	1775	93.0	93.6	93.7	92.9	0.83	0.78	0.68	8.5	2.5	3.7	IE3
575	Δ	60	15.00	-/-	20.00	1780	80.0	93.0	92.8	91.4	0.81	0.75	0.64	9.5	2.9	4.3	IE3
IM B3 / IM 1001		FS 160 L		127 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 16.4 s | 23.9 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	65.0 / 77.0 dB(A) ²⁾	69.0 / 81.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0850 kg m ²		Vibration severity grade	A
Bearing DE NDE	6309 Z C3	6309 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	10 g 10 g	8000 h	Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish C3
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	-/-		Motor protection	(G) 2 temperature sensors KTY84-130 (4 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	16.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_K/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer	
	title 1LE1603-1DB44-0AG4-Z F76+H01+Q01+Q11+R12			document number			
© Siemens AG 2021				rev. 01	creation date 2021-04-22 16:08	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3164B

SIMOTICS SD - 160 L - IM B3 - 4p

Special design

F76	Metal external fan	Q11	1/3 PTC thermistors - for tripping (2 terminals)
H01	Bolted on mounting feet (instead of cast)	R12	Terminal box rotated through 180°
Q01	Measuring nipple for SPM shock pulse measurement to monitor bearings		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1603-1DB44-0AG4-Z			document number				
© Siemens AG 2021	F76+H01+Q01+Q11+R12			rev. 01	creation date 2021-04-22 16:08	language en	Page 2/2	