

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3182A

SIMOTICS SD - 180 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta^{3)}$			$\cos\phi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_l/I_N	T_l/T_N	T_B/T_N	
500	Y	50	22.00	-/-	31.00	2950	71.0	92.7	93.2	92.9	0.89	0.86	0.79	7.5	2.3	3.5	IE3
575	Y	60	24.50	-/-	30.00	3550	66.0	91.7	92.0	91.4	0.89	0.86	0.79	7.7	2.3	3.6	IE3
575	Y	60	22.00	-/-	27.00	3560	59.0	91.7	91.8	90.9	0.89	0.89	0.80	9.0	2.5	3.9	IE3
IM B3 / IM 1001		FS 180 M		160 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 19.6 s | 29.9 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	73.0 / 80.0 dB(A) ²⁾	78.0 / 85.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.0800 kg m ²		Vibration severity grade	A
Bearing DE NDE	NU 310	6310 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	15 g 10 g 4000 h		Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish C3
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	16.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_K/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1603-1EA22-7AB4-Z D47+L22			document number				
© Siemens AG 2021				rev. 01	creation date 2021-04-22 22:43	language en	Page 1/2	

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3182A

SIMOTICS SD - 180 M - IM B3 - 2p

Special design

D47 TR CU product safety certificate EAC for the Eurasian Customs Union L22 Bearing design for increased cantilever forces

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1603-1EA22-7AB4-Z							
© Siemens AG 2021	D47+L22	rev. 01	creation date 2021-04-22 22:43		language en	Page 2/2		