

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3182A

SIMOTICS SD - 180 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	22.00	-/-	38.50	2950	71.0	92.7	93.2	92.9	0.89	0.86	0.79	7.5	2.3	3.5	IE3
690	Y	50	22.00	-/-	22.50	2950	71.0	92.7	93.2	92.9	0.89	0.86	0.79	7.5	2.3	3.5	IE3
460	Δ	60	24.50	-/-	37.50	3550	66.0	91.7	92.0	91.4	0.89	0.86	0.79	7.7	2.3	3.6	IE3
460	Δ	60	22.00	-/-	34.00	3560	59.0	91.7	91.8	90.9	0.89	0.89	0.80	9.0	2.5	3.9	IE3

IM B3 / IM 1001		FS 180 M	160 kg	IP55		IEC/EN 60034	IEC, DIN, ISO, VDE, EN										
-----------------	--	----------	--------	------	--	--------------	------------------------	--	--	--	--	--	--	--	--	--	--

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 19.6 s | 29.9 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	73.0 / 80.0 dB(A) ²⁾	78.0 / 85.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.0800 kg m ²		Vibration severity grade	A
Bearing DE NDE	6310 C3	6310 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	15 g 10 g 4000 h		Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish C3
Regreasing device	with regreasing nipple		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 71412 A		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	25.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27.0 mm - 35.0 mm
Type of terminal box	TB1 K01	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M6	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number		
	1LE1603-1EA23-4AB4-Z B02+L19+N30+Q01+Q02+R50+R62			
© Siemens AG 2021		rev.	creation date	language Page
		01	2021-04-23 16:43	en 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3182A

SIMOTICS SD - 180 M - IM B3 - 2p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	Q02	Anti-condensation heating for 230 V (2 terminals)
L19	Regreasing device with regreasing nipple M10X1 acc.to DIN 71412-A	R50	Larger terminal box
N30	Increased air humidity/temperature with 30 to 60 g water per m3 air	R62	Cast iron auxiliary terminal box (small)
Q01	Measuring nipple for SPM shock pulse measurement to monitor bearings		

Additional information:

Space heaters

Technical data: 1-phase, 230 V 50W

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released		customer			
	title 1LE1603-1EA23-4AB4-Z B02+L19+N30+Q01+Q02+R50+R62	document number					
© Siemens AG 2021		rev. 01	creation date 2021-04-23 16:43	language en	Page 2/2		