

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3184D

SIMOTICS SD - 180 L - IM V6 - 8p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	10.12	-/-	23.00	725	133.3	88.9	89.5	88.6	0.72	0.64	0.51	5.5	2.3	2.6	IE3
690	Y	50	10.12	-/-	13.30	725	133.3	88.9	89.5	88.6	0.72	0.64	0.51	5.5	2.3	2.6	IE3
IM V6 / IM 1031			FS 180 L			IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +50 °C / 1,000 m

Locked rotor time (hot / cold) : 33.9 s | 52.5 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	67 / 74 dB(A) ^{2) 3)}	71 / 78 dB(A) ^{2) 3)}	External earthing terminal	With (standard)
Moment of inertia	0.2600 kg m ²		Vibration severity grade	A
Bearing DE NDE	6310 C3	6310 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	20000 h	16000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	15 g 15 g	4000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	190 kg
Regreasing device	With (standard)		Coating (paint finish)	Special paint finish C3
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Condensate drainage holes	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type				document status		
	datasheet				released		
	title				document number		
	1LE1603-1ED43-4DB4-Z						
	N06+Q02				rev.	creation date	language Page
© Siemens AG 2023					943	2023-04-06	en 1/2

SIMOTICS SD - 180 L - IM V6 - 8p

N06	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 50°C, power reduced	Q02	Anti-condensation heating for 230 V (2 terminals)
-----	--	-----	---

Space heaters

Technical data:	1-phase, 230 V 50W
-----------------	--------------------

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1603-1ED43-4DB4-Z						
	N06+Q02			rev.	creation date	language	Page
© Siemens AG 2023				943	2023-04-06	en	2/2