

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3205A

SIMOTICS SD - 200 L - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
400	Δ	50	37.00	-/-	65.00	2955	120.0	93.7	94.2	94.0	0.88	0.85	0.78	7.1	2.5	3.2	IE3
690	Y	50	37.00	-/-	37.50	2955	120.0	93.7	94.2	94.0	0.88	0.85	0.78	7.1	2.5	3.2	IE3
460	Δ	60	41.50	-/-	63.00	3555	111.0	93.0	93.3	92.9	0.89	0.87	0.80	7.1	2.5	3.2	IE2
460	Δ	60	37.00	-/-	57.00	3560	99.0	93.0	93.1	92.3	0.88	0.85	0.77	7.6	2.7	3.3	IE3

IM B3 / IM 1001		FS 200 L		IP55		IEC/EN 60034	IEC, DIN, ISO, VDE, EN						
-----------------	--	----------	--	------	--	--------------	------------------------	--	--	--	--	--	--

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 28 s | 47.4 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	74 / 81 dB(A) ²⁾	79 / 86 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.1580 kg m ²		Vibration severity grade	A
Bearing DE NDE	NU 312	6312 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} , F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	20 g 20 g	4000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	250 kg
Regreasing device	Yes (standard)		Coating (paint finish)	Special paint finish C3
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	25 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M6	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_K/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_K/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number		
	1LE1603-2AA53-4AB4-Z			
	L22			
© Siemens AG 2021		rev.	creation date	language Page
		01	2021-10-11 21:43	en 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3205A

SIMOTICS SD - 200 L - IM B3 - 2p

Special design

L22 Bearing design for increased cantilever forces

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1603-2AA53-4AB4-Z							
© Siemens AG 2021	L22	rev. 01	creation date 2021-10-11 21:43		language en	Page 2/2		