

SIMOTICS SD - 200 L - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

-/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL	
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N		
DOL duty (S1) - 155(F) to 130(B)																		
400	Δ	50	37.00	-/-	65.00	2955	120.0	93.7	94.2	94.0	0.88	0.85	0.78	7.1	2.5	3.2	IE3	
690	Y	50	37.00	-/-	37.50	2955	120.0	93.7	94.2	94.0	0.88	0.85	0.78	7.1	2.5	3.2	IE3	
460	Δ	60	41.50	-/-	63.00	3555	111.0	93.0	93.3	92.9	0.89	0.87	0.80	7.1	2.5	3.2	IE2	
460	Δ	60	37.00	-/-	57.00	3560	99.0	93.0	93.1	92.3	0.88	0.85	0.77	7.6	2.7	3.3	IE3	
IM B3 / IM 1001			FS 200 L			IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN								
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 27.7 s 46.8 s									

Sound level (SPL / SWL) at 50Hz 60Hz	74 / 81 dB(A) ^{2) 3)}	79 / 86 dB(A) ^{2) 3)}	External earthing terminal	With (standard)
Moment of inertia	0.1580 kg m²		Vibration severity grade	A
Bearing DE NDE	6312 C3	6312 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	20 g 20 g 4000 h		Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	250 kg
Regreasing device	With (standard)		Coating (paint finish)	Special paint finish C3
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Condensate drainage holes	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box position	top	Max. cross-sectional area	35 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M8	Cable gland	4 plugs

Notes:

I_L/I_N = locked rotor current / current nominal	1) L_{10min} according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_L/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_b/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1603-2AA53-4AB4-Z						
	R50			rev.	creation date	language	Page
© INNOMOTICS 2023				951	2023-12-01	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3205A

SIMOTICS SD - 200 L - IM B3 - 2p

Special design

R50 Larger terminal box

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1LE1603-2AA53-4AB4-Z				document number
© INNOMOTICS 2023	R50	rev. 951	creation date 2023-12-01	language en	Page 2/2

