

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3226B

SIMOTICS SD - 225 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\phi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
400	Δ	50	55.00	-/-	98.00	1478	355.0	94.6	95.3	95.5	0.86	0.83	0.75	6.5	2.8	2.7	IE3
690	Y	50	55.00	-/-	57.00	1478	355.0	94.6	95.3	95.5	0.86	0.83	0.75	6.5	2.8	2.7	IE3
460	Δ	60	63.00	-/-	98.00	1778	340.0	94.1	94.6	94.7	0.86	0.84	0.76	6.5	2.8	2.6	IE2
460	Δ	60	55.00	-/-	85.00	1782	295.0	95.4	95.7	95.4	0.85	0.82	0.73	7.4	3.1	3.0	IE3
IM B5 / IM 3001		FS 225 M		415 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 36.5 s | 55.4 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	66.0 / 79.0 dB(A) ²⁾	68.0 / 82.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.6500 kg m ²		Vibration severity grade	A
Bearing DE NDE	6313 C3	6313 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	20 g 20 g	8000 h	Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish C3
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Type of bearing	Locating bearing DE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	35.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27.0 mm - 35.0 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M8	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_K/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type	datasheet		document status	released		
	title	1LE1603-2BB63-4FB4-Z		document number			
© Siemens AG 2021		B02+L20		rev.	creation date	language	Page
				01	2021-04-21 10:38	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3226B

SIMOTICS SD - 225 M - IM B5 - 4p

Special design

B02 Acceptance test certificate 3.1 acc. to EN 10204 L20 Locating bearing, DE

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet				document status released		customer	
	title 1LE1603-2BB63-4FB4-Z				document number			
© Siemens AG 2021	B02+L20				rev. 01	creation date 2021-04-21 10:38	language en	Page 2/2