

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3222D

SIMOTICS SD - 225 M - IM B3 - 8p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
230	Δ	50	22.00	-/-	79.00	732	285.0	90.6	91.4	91.2	0.77	0.71	0.59	5.9	2.6	2.9	IE3
400	Y	50	22.00	-/-	45.50	732	285.0	90.6	91.4	91.2	0.77	0.71	0.59	5.9	2.6	2.9	IE3
460	Y	60	26.50	-/-	46.00	882	285.0	91.7	92.4	92.0	0.79	0.74	0.63	5.9	2.4	2.8	IE3
460	Y	60	22.00	-/-	39.50	886	235.0	91.7	91.8	90.8	0.76	0.69	0.58	6.8	2.9	3.3	IE3
IM B3 / IM 1001		FS 225 M		280 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 21.9 s | 32.5 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	56.0 / 70.0 dB(A) ²⁾	60.0 / 74.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.5500 kg m ²		Vibration severity grade	A
Bearing DE NDE	NU 313	6313 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	20 g 20 g	8000 h	Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish C3
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	35.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27.0 mm - 35.0 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M8	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type	document status		customer			
	datasheet	released					
	title	document number					
	1LE1603-2BD22-2AB4-Z						
	F76+L22+R12						
© Siemens AG 2021	rev.	creation date		language	Page		
	01	2021-04-22 12:12		en	1/2		

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3222D

SIMOTICS SD - 225 M - IM B3 - 8p

Special design

F76	Metal external fan	R12	Terminal box rotated through 180°
L22	Bearing design for increased cantilever forces		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1603-2BD22-2AB4-Z			document number				
© Siemens AG 2021	F76+L22+R12			rev. 01	creation date 2021-04-22 12:12	language en	Page 2/2	