

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3256B

SIMOTICS SD - 250 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data	Safe Area
	-/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	75.00	-/-	235.00	1486	480.0	95.0	95.2	94.8	0.85	0.81	0.71	7.9	3.0	3.4	IE3
400	Y	50	75.00	-/-	134.00	1486	480.0	95.0	95.2	94.8	0.85	0.81	0.71	7.9	3.0	3.4	IE3
460	Y	60	86.00	-/-	132.00	1785	460.0	95.4	95.6	95.3	0.86	0.82	0.73	7.8	2.9	3.3	IE3
460	Y	60	75.00	-/-	117.00	1788	400.0	95.4	95.4	94.8	0.84	0.79	0.69	8.8	3.4	3.8	IE3
IM B3 / IM 1001		FS 250 M				IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 26.9 s 44.7 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	70 / 83 dB(A) ^{2) 3)}	74 / 88 dB(A) ^{2) 3)}	External earthing terminal	With (standard)
Moment of inertia	1.1000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6315 C3	6315 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} ¹⁾ for coupling operation 50 60Hz	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	25 g 25 g 8000 h		Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	510 kg
Regreasing device	With (standard)		Coating (paint finish)	Special paint finish C3
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Condensate drainage holes	With (standard)		Method of cooling	IC416 - separately ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	120 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 42 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal 1) L10mh according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411

M_A/M_N = locked rotor torque / torque nominal 2) at rated power / at full load

M_K/M_N = break down torque / nominal torque

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
IN LVM		SPC			
SIEMENS	document type				document status
	datasheet				released
	title				document number
	1LE1603-2CB62-2AB4-Z				
© INNOMOTICS 2023	F70+G11				rev.
					950
		creation date		language	Page
		2023-10-19		en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3256B

SIMOTICS SD - 250 M - IM B3 - 4p

Special design

F70

Mounting of separately driven fan

G11

Rotary pulse encoder Sendix 5020 (HTL)

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents			
	document type datasheet				document status released			
	title 1LE1603-2CB62-2AB4-Z				document number			
© INNOMOTICS 2023	F70+G11				rev. 950	creation date 2023-10-19	language en	Page 2/2