

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3280A

SIMOTICS SD - 280 S - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	75.00	-/-	128.00	2975	240.0	94.7	94.8	94.1	0.89	0.87	0.80	6.8	2.4	3.0	IE3
690	Y	50	75.00	-/-	74.00	2975	240.0	94.7	94.8	94.1	0.89	0.87	0.80	6.8	2.4	3.0	IE3
460	Δ	60	84.00	-/-	125.00	3575	225.0	94.5	94.4	93.5	0.89	0.87	0.81	6.8	2.5	3.0	IE2
460	Δ	60	75.00	-/-	112.00	3578	200.0	94.1	93.9	92.7	0.89	0.87	0.79	7.6	2.7	3.2	IE3
IM B3 / IM 1001		FS 280 S		510 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 31.2 s | 55.3 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	74.0 / 88.0 dB(A) ²⁾	78.0 / 92.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.7700 kg m ²		Vibration severity grade	A
Bearing DE NDE	6315 C3	6315 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	25 g 25 g 4000 h		Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish C3
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	120.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34.0 mm - 42.0 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator						
	document type			document status		customer		
	datasheet			released				
© Siemens AG 2021	title			document number				
	1LE1603-2DA03-4AB4-Z							
	L05			rev.	creation date	language	Page	
				01	2021-04-20 22:28	en	1/2	

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3280A

SIMOTICS SD - 280 S - IM B3 - 2p

Special design

L05

Second standard shaft extension

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1603-2DA03-4AB4-Z						
	L05			rev.	creation date	language	Page
© Siemens AG 2021				01	2021-04-20 22:28	en	2/2