

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3280B

SIMOTICS SD - 280 S - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	75.00	-/-	133.00	1485	480.0	95.0	95.3	95.0	0.86	0.83	0.75	6.9	2.5	3.0	IE3
690	Y	50	75.00	-/-	77.00	1485	480.0	95.0	95.3	95.0	0.86	0.83	0.75	6.9	2.5	3.0	IE3
460	Δ	60	86.00	-/-	131.00	1785	460.0	94.5	94.7	94.2	0.87	0.85	0.77	6.8	2.5	2.9	IE2
460	Δ	60	75.00	-/-	116.00	1788	400.0	95.4	95.3	94.5	0.85	0.81	0.72	7.7	2.8	3.3	IE3
IM B3 / IM 1001		FS 280 S		570 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - + °C / 1,000 m

Locked rotor time (hot / cold) : 31.2 s | 47.7 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	69.0 / 83.0 dB(A) ²⁾	77.0 / 91.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	1.3900 kg m ²		Vibration severity grade	A
Bearing DE NDE	6317 C3	6317 C3	Insulation	155(F) to 155(F)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	30 g	30 g	Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish C3
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	120.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34.0 mm - 42.0 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1603-2DB03-4AB4-Z						
	B02+H01+H07+N03			rev.	creation date	language	Page
© Siemens AG 2021				01	2021-04-23 15:56	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3280B

SIMOTICS SD - 280 S - IM B3 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	H07	Stainless steel screws and bolts (outside the motor)
H01	Bolted on mounting feet (instead of cast)	N03	Temperature class 155 (F), utilised to 155 (F), with increased cooling medium temperature

Notes:

responsible dep. DI MC LVM		technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
		document type datasheet			document status released		customer	
		title 1LE1603-2DB03-4AB4-Z			document number			
© Siemens AG 2021		B02+H01+H07+N03			rev.	creation date	language	Page
					01	2021-04-23 15:56	en	2/2