

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3280B

SIMOTICS SD - 280 S - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 155(F)																	
400	Δ	50	75.00	-/-	133.00	1485	480.0	95.0	95.3	95.0	0.86	0.83	0.75	6.9	2.5	3.0	IE3
690	Y	50	75.00	-/-	77.00	1485	480.0	95.0	95.3	95.0	0.86	0.83	0.75	6.9	2.5	3.0	IE3
460	Δ	60	86.00	-/-	131.00	1785	460.0	94.5	94.7	94.2	0.87	0.85	0.77	6.8	2.5	2.9	IE2
460	Δ	60	75.00	-/-	116.00	1788	400.0	95.4	95.3	94.5	0.85	0.81	0.72	7.7	2.8	3.3	IE3
IM B3 / IM 1001			FS 280 S			IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - + °C / 1,000 m									Locked rotor time (hot / cold) : 31.2 s 47.7 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	69 / 83 dB(A) ²⁾	77 / 91 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	1.3900 kg m ²		Vibration severity grade	A
Bearing DE NDE	6317 C3	6317 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} min ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
50 60Hz			Frame material	cast iron
Relubrication interval/quantity DE	30 g 30 g		Net weight of the motor (IM B3)	570 kg
NDE			Coating (paint finish)	Special paint finish C3
Lubricants	Unirex N3		Color, paint shade	RAL7030
Regreasing device	Yes (standard)		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Grease nipple	M10x1 DIN 3404 A		Method of cooling	IC411 - self ventilated, surface cooled
Type of bearing	Locating bearing NDE			
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	120 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 42 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10	Cable gland	4 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
DI MC LVM		DT Configurator			
	document type				document status
	datasheet				released
	title				document number
	1LE1603-2DB03-4AB4-Z				
© Siemens AG 2022	N03				rev.
					01
					creation date
					2022-02-02
					language
					en
					Page
					1/2



Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3280B

SIMOTICS SD - 280 S - IM B3 - 4p

Special design

N03 Temperature class 155 (F), utilised to 155 (F), with increased cooling medium temperature

Notes:

responsible dep.

DI MC LVM

technical reference

created by

DT Configurator

approved by

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

[Link documents](#)

SIEMENS

document type

datasheet

title

1LE1603-2DB03-4AB4-Z

N03

document status

released

document number

rev.

01

creation date

2022-02-02

language

en

Page

2/2