

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3314C

SIMOTICS SD - 315 L - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
500	Δ	50	110.00	-/-	159.00	991	1060.0	95.1	95.5	95.3	0.84	0.80	0.71	7.2	2.8	3.0	IE3
575	Δ	60	132.00	-/-	164.00	1190	1060.0	95.0	95.4	95.3	0.85	0.82	0.74	7.0	2.7	2.8	IE2
575	Δ	60	110.00	-/-	139.00	1192	880.0	95.8	95.9	95.5	0.83	0.79	0.69	8.2	3.2	3.4	IE3
IM B3 / IM 1001		FS 315 L		990 kg		IP55	IEC/EN 60034		IEC, DIN, ISO, VDE, EN								
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 33.7 s 49.9 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	63.0 / 78.0 dB(A) ²⁾	64.0 / 79.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	3.9000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6319 C3	6319 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h		Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish C3
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(G) 2 temperature sensors KTY84-130 (4 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	240.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38.0 mm - 45.0 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M12	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_A/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
SIEMENS	document type	datasheet		document status		customer	
	title	1LE1603-3AC44-0AG4-Z		released			
© Siemens AG 2021		F76+H01+Q01+Q11+R12		document number			
				rev.	creation date	language	Page
				01	2021-04-22 16:10	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3314C

SIMOTICS SD - 315 L - IM B3 - 6p

Special design

F76	Metal external fan	Q11	1/3 PTC thermistors - for tripping (2 terminals)
H01	Bolted on mounting feet (instead of cast)	R12	Terminal box rotated through 180°
Q01	Measuring nipple for SPM shock pulse measurement to monitor bearings		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1603-3AC44-0AG4-Z							
© Siemens AG 2021	F76+H01+Q01+Q11+R12	rev. 01	creation date 2021-04-22 16:10		language en	Page 2/2		