

SIMOTICS SD - 132 S - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Safe Area

-/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
380	Δ	50	5.50	-/-	11.00	1470	35.5	91.9	92.5	92.3	0.83	0.78	0.68	8.3	2.6	3.5	IE4
660	Y	50	5.50	-/-	6.30	1470	35.5	91.9	92.5	92.3	0.83	0.78	0.68	8.3	2.6	3.5	IE4
440	Δ	60	6.30	-/-	10.80	1770	34.0	92.4	92.9	92.6	0.83	0.79	0.70	8.3	2.5	3.5	IE4
440	Δ	60	5.50	-/-	9.50	1770	29.5	92.4	92.6	91.9	0.82	0.77	0.66	9.4	2.9	4.1	IE4
IM B5 / IM 3001			FS 132 S			IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN						Grade 2	
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 27.5 s 34.9 s								

Sound level (SPL / SWL) at 50Hz 60Hz	56 / 68 dB(A) ^{2) 3)}	61 / 73 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0340 kg m²		Thermal class	F
Bearing DE NDE	6308 2Z C3	6308 2Z C3 INS	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad,min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	77 kg
Grease nipple	-/-		Coating (paint finish)	Special paint finish C3
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Bearing insulation DE / Bearing insulation NDE	Yes (non-drive end)		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Condensate drainage holes	With (standard)		Method of cooling	IC416 - separately ventilated, surface cooled
External earthing terminal	Without			

Terminal box position	top	Max. cross-sectional area	6 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 J01	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	1 gland, 2 plugs

I_{r}/I_{n} = locked rotor current / current nominal	1) $L_{10\text{th}}$ according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_r/M_n = locked rotor torque / torque nominal	2) at rated power / at full load	
M_b/M_n = break down torque / nominal torque		

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	Document type Technical data sheet			Document status Released			
	Document title 1LE1604-1CB03-3FB4-Z			Document number TDS-240329-101356			
Restricted © Innomotics 2024	B02+D34+F01+F12+F50+F70+G04+H70+L51+R15+R50+R62			Revision AA	Creation date 2024-03-29	Language en	Page 1/2

SIMOTICS SD - 132 S - IM B5 - 4p

B02	Acceptance test certificate 3.1 acc. to EN 10204	G04	Mounted rotary pulse encoder LL 861 900 220
D34	China Energy Efficiency Label	H70	Second outer earthing
F01	Mounting of holding brake	L51	Bearing insulation NDE
F12	Brake supply voltage 400 V AC, 50/60 Hz	R15	One metal cable gland
F50	Mechanical manual brake release with lever (cannot be locked)	R50	Larger terminal box
F70	Mounting of separately driven fan	R62	Cast iron auxiliary terminal box (small)

Brake:

Description:	BFK458-16	Current:	.31 A
Voltage:	AC 400 V	Moment of inertia:	0.001500 kam ²

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference SPC	Created by Created automatically	Approved by Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	Document type Technical data sheet		Document status Released			
	Document title 1LE1604-1CB03-3FB4-Z		Document number TDS-240329-101356			
Restricted © Innomotics 2024	B02+D34+F01+F12+F50+F70+G04+H70+L51+R15+R50+R62		Revision AA	Creation date 2024-03-29	Language en	Page 2/2