

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4164B

SIMOTICS SD - 160 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	15.00	-/-	50.00	1480	97.0	93.9	94.0	93.3	0.80	0.74	0.62	7.8	3.7	4.3	IE4
400	Y	50	15.00	-/-	29.00	1480	97.0	93.9	94.0	93.3	0.80	0.74	0.62	7.8	3.7	4.3	IE4
460	Y	60	17.30	-/-	28.50	1780	93.0	94.5	94.6	94.0	0.81	0.76	0.64	7.9	3.4	4.2	IE4
460	Y	60	15.00	-/-	25.50	1780	80.0	94.1	94.0	93.0	0.79	0.72	0.60	8.8	3.9	4.8	IE4
IM B3 / IM 1001		FS 160 L				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 33.1 s 43.6 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz/60Hz	75 / 79 dB(A) ²⁾	75 / 79 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0990 kg m ²		Vibration severity grade	A
Bearing DE NDE	6309 Z C3	6309 Z C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} min ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
50/60Hz			Frame material	cast iron
Relubrication interval/quantity DE NDE	10 g 10 g	8000 h	Net weight of the motor (IM B3)	138 kg
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish C3
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M8x1 DIN 71412		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC416 - separately ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
DI MC LVM		DT Configurator			
	document type				document status
	datasheet				released
	title				document number
	1LE1604-1DB42-2AB4-Z				
© Siemens AG 2022	F70+G11+M01				rev.
					01
				creation date	2022-04-27
				language	en
				Page	1/2



Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4164B

SIMOTICS SD - 160 L - IM B3 - 4p

Special design

F70	Mounting of separately driven fan	M01	Connection when shipped, star connection
G11	Rotary pulse encoder Sendix 5020 (HTL)		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				
	title 1LE1604-1DB42-2AB4-Z F70+G11+M01				
© Siemens AG 2022		rev. 01	creation date 2022-04-27	language en	Page 2/2