

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4220B

SIMOTICS SD - 225 S - IM B7 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	37.00	-/-	67.00	1485	240.0	95.2	95.5	95.2	0.84	0.80	0.70	8.4	3.2	3.2	IE4
690	Y	50	37.00	-/-	38.50	1485	240.0	95.2	95.5	95.2	0.84	0.80	0.70	8.4	3.2	3.2	IE4
460	Δ	60	42.50	-/-	66.00	1782	230.0	95.4	95.6	95.3	0.85	0.81	0.72	8.5	3.1	3.1	IE4
460	Δ	60	37.00	-/-	59.00	1786	198.0	95.4	95.4	94.8	0.83	0.78	0.68	9.8	3.6	3.6	IE4
IM B7 / IM 1061		FS 225 S				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 35.2 s 46.8 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	69 / 82 dB(A) ^{2) 3)}	69 / 81 dB(A) ^{2) 3)}	External earthing terminal	Yes (standard)
Moment of inertia	0.5200 kg m ²		Vibration severity grade	A
Bearing DE NDE	6313 C3	6313 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} ¹⁾ for coupling operation 50 60Hz	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	20 g 20 g 8000 h		Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	345 kg
Regreasing device	Yes (standard)		Coating (paint finish)	Special paint finish C3
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(K) 1 Pt1000 resistance thermometer(2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	left	Max. cross-sectional area	35 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M8	Cable gland	4 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _A /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _K /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
DI MC LVM		DT Configurator			
	document type				document status
	datasheet				released
	title				document number
	1LE1604-2BB03-4UK6-Z Q35				
© Siemens AG 2022		rev.	creation date	language	Page
		01	2022-08-12	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4220B

SIMOTICS SD - 225 S - IM B7 - 4p

Special design

Q35 1 Pt1000 resistance thermometer (2 terminals)

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1LE1604-2BB03-4UK6-Z Q35				document number
© Siemens AG 2022				rev. 01	creation date 2022-08-12
				language en	Page 2/2

