

SD motor type: 1CV4315B low-voltage motor, IEC squirrel-cage rotor, self-cooled, IP55 temperature class 155(F) according to 130(B) gray cast iron housing Performance Line Super Premium Efficiency IE4, 4-pole * size 315L, * 200 kW (50 Hz) 230 kW (60 Hz) standard color RAL 7030 if no order code is specified for selecting another color. The product will be delivered with either the Siemens or Innomotics product brand. 3 AC 50 Hz 400 VD/690 VY * 3 AC 60 Hz 460 VD IM V 1 without canopy, Flange: FF600 (A660) 6 PTC thermistors for warning and shutdown (4 terminals) Terminal box at top Q01=Measuring nipple for SPM shock pulse measurement for bearing inspection Q02=Anti-condensation heating for 230 V (2 terminals) Q60=3 resistance thermometers Pt100-2 conductor circuit (6 terminals) Q72=2 resistance thermometers Pt100 in basic configuration for bearing (4 terminals) R62=Auxiliary terminal box cast iron (small)

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com>

