

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3314B

SIMOTICS SD - 315 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
380	Δ	50	147.20	-/-	270.00	1490	943.5	95.9	96.1	96.1	0.86	0.83	0.74	7.9	3.1	3.4	IE3
440	Δ	60	169.28	-/-	265.00	1785	905.7	96.3	96.5	96.2	0.87	0.84	0.77	7.8	3.3	3.1	IE3
440	Δ	60	150.00	200.00	235.00	1791	800.0	96.2	96.2	95.7	0.87	0.84	0.75	8.8	3.5	3.6	MG1
IM B3 / IM 1001		FS 315 L		990 kg		IP65	CC032A	IEC/EN 60034		IEC, EN, UL, CSA, NEMA MG1-12-12				kVA Code: K			

Environmental conditions : -20 °C - +50 °C / 1,000 m

Locked rotor time (hot / cold) : 27.3 s | 45.9 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	73.0 / 87.0 dB(A) ²⁾	78.0 / 92.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	3.1000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6319 C3	6319 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	40 g 40 g 3000 h		Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish C3
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Type of bearing	Locating bearing DE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	240.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38.0 mm - 45.0 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M12	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1623-3AB43-3AB4-Z H20+L51+N06			document number				
© Siemens AG 2021				rev. 01	creation date 2021-04-21 13:29	language en	Page 1/2	

SIMOTICS SD - 315 L - IM B3 - 4p

H20	IP 65 degree of protection	N06	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 50°C, power reduced
L51	Bearing insulation NDE		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	title 1LE1623-3AB43-3AB4-Z			document status released		customer	
	H20+L51+N06				document number			
© Siemens AG 2021			rev. 01	creation date 2021-04-21 13:29	language en	Page 2/2		