

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3104B

SIMOTICS SD - 100 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	2.20	-/-	4.40	1465	14.3	86.7	87.0	85.9	0.83	0.77	0.66	8.4	3.2	4.4	IE3
690	Y	50	2.20	-/-	2.55	1465	14.3	86.7	87.0	85.9	0.83	0.77	0.66	8.4	3.2	4.4	IE3
460	Δ	60	2.54	-/-	4.25	1765	13.8	89.5	89.7	88.5	0.84	0.81	0.69	8.5	3.0	4.4	IE3
460	Δ	60	2.20	-/-	3.80	1770	11.9	89.5	89.2	87.2	0.81	0.75	0.63	9.6	3.5	5.1	IE3
IM B3 / IM 1001		FS 100 L		40 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN						KS C IEC60034-2-1	

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 19 s | 22.6 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	60.0 / 72.0 dB(A) ²⁾	62.0 / 74.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0140 kg m ²		Vibration severity grade	A
Bearing DE NDE	6306 2Z C3	6306 2Z C3	Insulation	180(H) to 180(H)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Special paint finish C3
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	4.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 F01	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	2 glands, 1 plug

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1643-1AB43-4AB4-Z B02+H70+N10+R11+R18+Y82			document number				
© Siemens AG 2021				rev. 01	creation date 2021-04-20 20:50	language en	Page 1/2	

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3104B

SIMOTICS SD - 100 L - IM B3 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	R11	Terminal box rotated through 90°, cable entry from NDE
H70	Second outer earthing	R18	Cable gland metal, max. number
N10	Temperature class 180 (H)	Y82	Auxiliary name plate with customer data

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1643-1AB43-4AB4-Z			document number				
© Siemens AG 2021	B02+H70+N10+R11+R18+Y82			rev. 01	creation date 2021-04-20 20:50	language en	Page 2/2	