

SIMOTICS SD - - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
IM B3 / IM 1001			FS		760 kg		IP55			IEC/EN 60034	IEC, DIN, ISO, VDE, EN			KS C IEC60034-2-1			

Locked rotor time (hot / cold) : 37.3 s | 59.4 s

Sound level (SPL / SWL) at 50Hz 60Hz	72.9 / 87.3 dB(A) ²⁾	76.7 / 91.1 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	2.2000 kg m²		Vibration severity grade	A
Bearing DE NDE	6319 C3	6319 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	40 g	40 g	Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish C3
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(K) 1 Pt1000 resistance thermometer(2 terminals)
Type of bearing	Locating bearing DE		Method of cooling	IC416 - separately ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box position	top	Max. cross-sectional area	240.0 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	38.0 mm - 45.0 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M12	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1643-3AB09-0AK4-Z						
© Siemens AG 2021	D33+F70+G04+L51+M1Y+N30+R62+Y50+Y81+Y82			rev.	creation date	language	Page
				01	2021-05-07 10:08	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3310B

SIMOTICS SD - - IM B3 - 4p

Special design

D33	For Korea, certified according to KS C IEC 60034-2-1	N30	Increased air humidity/temperature with 30 to 60 g water per m3 air
F70	Mounting of separately driven fan	R62	Cast iron auxiliary terminal box (small)
G04	Mounted rotary pulse encoder LL 861 900 220	Y50	Temperature class 155(F), utilized acc. to 130(B), customer indication of coolant temperature and/or installation altitude
L51	Bearing insulation NDE	Y81	External fan with non-standard voltage and/or frequency:
M1Y	Non-standard winding:	Y82	Auxiliary name plate with customer data

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1643-3AB09-0AK4-Z							document number
© Siemens AG 2021	D33+F70+G04+L51+M1Y+N30+R62+Y50+Y81+Y82	rev. 01	creation date 2021-05-07 10:08		language en	Page 2/2		