

SIMOTICS SD - 315 L - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

-/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	250.00	-/-	430.00	2986	800.0	95.8	95.7	95.0	0.88	0.85	0.77	9.3	3.0	4.2	IE3
690	Y	50	250.00	-/-	250.00	2986	800.0	95.8	95.7	95.0	0.88	0.85	0.77	9.3	3.0	4.2	IE3
460	Δ	60	250.00	-/-	370.00	3588	670.0	95.8	95.4	94.4	0.88	0.84	0.76	11.0	4.1	4.6	IE3
460	Δ	60	280.00	-/-	415.00	3586	750.0	95.8	95.5	94.7	0.88	0.85	0.78	9.6	3.7	4.1	IE3
IM B3 / IM1001			FS 315 L				IP55	UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 27.4 s 43.2 s								

Sound level (SPL / SWL) at 50Hz 60Hz	80 / 94 dB(A) ^{2) 3)}	84 / 98 dB(A) ^{2) 3)}	Condensate drainage holes	(Standard) Yes	
Moment of inertia	2.8200 kg m²		External earthing terminal	(Standard) Yes	
Bearing DE NDE	6316 C4	6316 C4	Vibration severity grade	Grade A	
permissible lateral force on (N) (N)	X ₀ : 5800	X _{0.5} : 5500	X _{max} : 5200	Thermal class	F
bearing lifetime			Duty type	S1	
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional	
Relubrication interval/quantity DE NDE	30 g 30 g 3000 h		Frame material	cast iron	
Lubricants	UNIREX N3		Net weight of the motor	1340 kg	
Regreasing device	-/-		Coating (paint finish)	Standard paint finish C2	
Grease nipple	-/-		Color, paint shade	RAL7030	
Type of bearing	Locating bearing DE		Motor protection	3 PTC thermistors - for tripping (2 terminals)	
Bearing insulation DE / Bearing insulation NDE	Yes (Non-drive end)		Method of cooling	IC411 - self ventilated, surface cooled	

Terminal box position	box at the top, socket right	Max. cross-sectional area	240 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	42 mm - 54 mm
Type of terminal box	TB3Q61	Cable entry	2xM63x1,5 - 2xM20x1,5
Contact screw thread	6xM12	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE5503-3AA63-4AB1-Z						
© INNOMOTICS 2023	L51			rev.	creation date	language	Page
				951	2023-12-14	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3316A

SIMOTICS SD - 315 L - IM B3 - 2p

Special design

L51 Bearing insulation NDE

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1LE5503-3AA63-4AB1-Z				document number
© INNOMOTICS 2023	L51				rev. 951
					creation date 2023-12-14
					language en
					Page 2/2

