

SD motor type: 1CV3317B low-voltage motor, IEC squirrel-cage rotor, self-cooled, IP55 temperature class 155(F) according to 130(B) gray cast iron housing Basic Line Premium Efficiency IE3, 4-pole * size 315L* 315 kW (50 Hz) standard color RAL 7030 if no order code is specified for selecting another color. Purchase of this product is exclusively governed by the Innomotics T&Cs located at <https://www.innomotics.com/terms-and-conditions> 3 AC 50HZ 400VD/690VY * 3 AC 60HZ 460VD IM B 3, 6 PTC thermistors for warning and shutdown (4 terminals) terminal box base right with inclined terminal box 45° B02=Acceptance test certificate 3.1 according to EN 10204 F74=Sheet metal fan cover H07=Stainless screws (external) L22=Bearing for increased transverse forces N08=Temperature class 155 (F), utilized according to 130(B), coolant temperature 60 °C, derating approx. 18% Q02=Anti-condensation heating for 230 V (2 terminals) R11=Terminal box rotated by 90°, entry from NDE NDE R62=Auxiliary terminal box cast iron (small) S02=Special paint finish Y56=PAINT FINISH IN SPECIAL RAL COLOURS (SELECTION SEE CATALOG) RAL.... Y58=Non-standard cylindrical shaft extension, DE (DE) Y82=Extra rating plate with customer data (no modified motor operating data permissible) Y99=Special motor design

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com>

