

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3317B

SIMOTICS SD - 315 L - IM V1 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Safe Area																	
Electrical data																	
U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	315.00	-/-	570.00	1490	2000.0	96.0	96.0	95.6	0.83	0.80	0.70	8.5	3.2	3.5	IE3
690	Y	50	315.00	-/-	330.00	1490	2000.0	96.0	96.0	95.6	0.83	0.80	0.70	8.5	3.2	3.5	IE3
460	Δ	60	315.00	-/-	495.00	1792	1680.0	96.2	96.0	95.3	0.83	0.78	0.69	9.4	3.4	3.7	IE3
460	Δ	60	360.00	-/-	560.00	1790	1920.0	96.2	96.1	95.6	0.84	0.80	0.72	8.3	3.0	3.2	IE3
IM V1 / IM3011			FS 315 L		IP55		UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN, GB 18613-2012						Grade 3	
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 20.7 s 41.4 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	75 / 90 dB(A) ^{2) 3)}	81 / 95 dB(A) ^{2) 3)}	External earthing terminal	(Standard) Yes
Moment of inertia	5.3900 kg m ²		Vibration severity grade	Grade A
Bearing DE NDE	6319 C4	7319 B	Thermal class	F
permissible lateral force on (N)	X ₀ : 9300	X _{0.5} : 8650	Duty type	S1
		X _{max} : 8000	Direction of rotation	bidirectional
bearing lifetime			Frame material	cast iron
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	20000 h	16000 h	Net weight of the motor	1653 kg
Relubrication interval/quantity DE NDE	40 g 40 g	6000 h	Coating (paint finish)	Standard paint finish C2
Lubricants	UNIREX N3		Color, paint shade	RAL7030
Regreasing device	-/-		Motor protection	3 PTC thermistors - for tripping (2 terminals)
Grease nipple	-/-		Method of cooling	IC411 - self ventilated, surface cooled
Type of bearing	Locating bearing NDE			
Condensate drainage holes	(Standard) Yes			

Terminal box

Terminal box position	box at the angle 45°, socket right	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	42 mm - 54 mm
Type of terminal box	TB3Q61	Cable entry	2xM63x1,5 - 2xM20x1,5
Contact screw thread	6xM12	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque
1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents 	
SIEMENS	document type datasheet			document status released			
	title 1LE5503-3AB73-4GB3-Z			document number			
© INNOMOTICS 2023	D34			rev. 951	creation date 2023-12-14	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3317B

SIMOTICS SD - 315 L - IM V1 - 4p

Special design

D34

China Energy Efficiency Label

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1LE5503-3AB73-4GB3-Z				document number
© INNOMOTICS 2023				rev. 951	creation date 2023-12-14
				language en	Page 2/2

