

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4282B

SIMOTICS SD - 280 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Safe Area																		
Electrical data								-/-										
U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL	
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N		
DOL duty (S1) - 155(F) to 130(B)																		
380	Δ	50	90.00	-/-	162.00	1488	580.0	96.1	96.4	96.3	0.88	0.85	0.78	8.5	2.8	3.4	IE4	
660	Y	50	90.00	-/-	93.00	1488	580.0	96.1	96.4	96.3	0.88	0.85	0.78	8.5	2.8	3.4	IE4	
440	Δ	60	90.00	-/-	141.00	1790	480.0	96.2	96.3	95.9	0.87	0.84	0.75	9.8	3.2	3.7	IE4	
440	Δ	60	104.00	-/-	161.00	1788	560.0	96.2	96.4	96.3	0.88	0.86	0.79	8.7	2.8	3.2	IE4	
IM B3 / IM1001			FS 280 M				IP55	UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 29.5 s 43.7 s									

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	67 / 81 dB(A) ^{2) 3)}	74 / 88 dB(A) ^{2) 3)}	External earthing terminal	(Standard) Yes
Moment of inertia	2.0300 kg m ²		Vibration severity grade	Grade A
Bearing DE NDE	6316 C3 S0	6316 C3 S0	Thermal class	F
permissible lateral force on (N)	X ₀ : 8600	X _{0.5} : 7900	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Relubrication interval/quantity DE NDE	30 g 30 g 8000 h		Net weight of the motor	681 kg
Lubricants	UNIREX N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	Flat type lubricating nipple		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	3 PTC thermistors - for tripping (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	(Standard) Yes			

Terminal box

Terminal box position	box at the top	Max. cross-sectional area	120 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 45 mm
Type of terminal box	TB4N01	Cable entry	2xM63x1,5 - 2xM20x1,5
Contact screw thread	6xM10	Cable gland	-/-

Notes:		
I_L/I_N = locked rotor current / current nominal	1) L_{10mh} according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_L/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_B/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type	datasheet			document status		
	title	1LE5504-2DB23-3AB4-Z			document number		
© INNOMOTICS 2024	D47			rev.	creation date	language	Page
				953	2024-02-19	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4282B

SIMOTICS SD - 280 M - IM B3 - 4p

Special design

D47

TR CU product safety certificate EAC for the Eurasian Customs Union

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE5504-2DB23-3AB4-Z			document number			
© INNOMOTICS 2024	D47			rev. 953	creation date 2024-02-19	language en	Page 2/2