

SIMOTICS SD - 315 M - IM V1 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

-/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	132.00	-/-	220.00	2988	420.0	96.2	96.2	95.6	0.90	0.88	0.81	9.8	2.6	3.9	IE4
690	Y	50	132.00	-/-	128.00	2988	420.0	96.2	96.2	95.6	0.90	0.88	0.81	9.8	2.6	3.9	IE4
460	Δ	60	132.00	-/-	192.00	3590	350.0	95.8	95.5	94.4	0.90	0.87	0.80	11.0	2.9	4.3	IE4
460	Δ	60	148.00	-/-	215.00	3588	395.0	95.8	95.6	94.8	0.90	0.88	0.82	9.8	2.6	3.9	IE4
IM V1 / IM3011			FS 315 M			IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 27.2 s 41.3 s								

Sound level (SPL / SWL) at 50Hz 60Hz	69 / 84 dB(A) ^{2) 3)}	73 / 88 dB(A) ^{2) 3)}	External earthing terminal	(Standard) Yes	
Moment of inertia	2.0800 kg m²		Vibration severity grade	Grade A	
Bearing DE NDE	6316 C3	6316 C3	Thermal class	F	
permissible lateral force on (N) (N)	X ₀ : 5800	X _{0.5} : 5500	X _{max} : 5200	Duty type	S1
bearing lifetime			Direction of rotation	counter-clockwise	
L _{10mh} F _{Rad,min} for coupling operation 50 60Hz ¹⁾	20000 h	16000 h	Frame material	cast iron	
Relubrication interval/quantity DE NDE	30 g 30 g 3000 h		Net weight of the motor	1050 kg	
Lubricants	UNIREX N3		Coating (paint finish)	Special paint finish C3	
Regreasing device	Flat type lubricating nipple		Color, paint shade	RAL7030	
Grease nipple	M10x1 DIN 3404 A		Motor protection	3 PTC thermistors - for tripping (2 terminals)	
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled	
Condensate drainage holes	(Standard) Yes				

Terminal box position	box at the top	Max. cross-sectional area	240 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 45 mm
Type of terminal box	TB1Q01	Cable entry	2xM63x1,5 - 2xM20x1,5
Contact screw thread	6xM12	Cable gland	4 plugs

Notes:

I_L/I_N = locked rotor current / current nominal	1) L_{10min} according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_L/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_b/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE5504-3AA23-4GB4-Z						
	B02+F78+S02+Y82						
© INNOMOTICS 2024				rev.	creation date	language	Page
				953	2024-02-27	en	1/2

SIMOTICS SD - 315 M - IM V1 - 2p

B02	Acceptance test certificate 3.1 acc. to EN 10204	S02	Special paint finish C3
F78	Low-noise version for 2-pole motors, for counter-clockwise direction of rotation	Y82	Auxiliary name plate with customer data

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	document type datasheet			document status released			
	title 1LE5504-3AA23-4GB4-Z			document number			
© INNOMOTICS 2024	B02+F78+S02+Y82			rev. 953	creation date 2024-02-27	language en	Page 2/2