

SD motor type: 1CV4314A low-voltage motor, IEC squirrel-cage rotor, self-cooled, IP55 temperature class 155(F) according to 130(B) gray cast iron housing Basic Line Premium Efficiency IE4 2-pole * size 315L 160 kW (50 Hz) standard color RAL 7030 if no order code is specified for selecting another color. Purchase of this product is exclusively governed by the Innomotics T&Cs located at <https://www.innomotics.com/terms-and-conditions> 3 AC 50 Hz 400 VD/690 VY * 3 AC 60 Hz 460 VD IM B3 3 PTC thermistors for disconnection (2 terminals) terminal box at top B02=Acceptance test certificate 3.1 according to EN 10204 F76=with external metal fan L22=Bearing for increased transverse forces N08=Temperature class 155 (F), utilized according to 130(B), coolant temperature 60 °C, derating approx. 18% Q02=Anti-condensation heating for 230 V (2 terminals) R11=Terminal box rotated by 90°, entry from NDE NDE R62=Auxiliary terminal box cast iron (small) S02=special paint finish Y53=Paint finish in other standard RAL colors (for selection see catalog) RAL... Y82=Extra rating plate with customer data (no modified motor operating data permissible)

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)

<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-VW>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com>

