

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4310B

SIMOTICS SD - 315 S - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

Electrical data -/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	110.00	-/-	335.00	1491	700.0	96.3	96.4	96.0	0.86	0.83	0.74	8.6	3.3	3.3	IE4
400	Y	50	110.00	-/-	192.00	1491	700.0	96.3	96.4	96.0	0.86	0.83	0.74	8.6	3.3	3.3	IE4
460	Y	60	127.00	-/-	193.00	1790	680.0	96.2	96.2	95.8	0.86	0.83	0.76	8.5	3.2	3.1	IE4
IM B3 / IM1001			FS 315 S		IP55		UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 30.8 s 44.1 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	66 / 80 dB(A) ^{2) 3)}	71 / 85 dB(A) ^{2) 3)}	Condensate drainage holes	(Standard) Yes
Moment of inertia	2.7400 kg m ²		External earthing terminal	(Standard) Yes
Bearing DE NDE	NU 319	6319 C3	Vibration severity grade	Grade A
permissible lateral force on (N) (N)	X ₀ : 34000	X _{0.5} : 23000	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad, min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h		Frame material	cast iron
Lubricants	UNIREX N3		Net weight of the motor	922 kg
Regreasing device	Flat type lubricating nipple		Coating (paint finish)	Standard paint finish C2
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	1 temperature sensor KTY84-130 (2 terminals)
Bearing insulation DE / Bearing insulation NDE	Yes (Non-drive end)		Method of cooling	IC416 - separately ventilated, surface cooled

Terminal box

Terminal box position	box at the top	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 45 mm
Type of terminal box	TB1Q01	Cable entry	2xM63x1,5 - 2xM20x1,5
Contact screw thread	6xM12	Cable gland	4 plugs

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power I at full load
3) Value is valid only for DOL operation with motor design IC411

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents 	
	Document type Technical data sheet			Document status Released			
	Document title 1LE5504-3AB02-2AF4-Z			Document number TDS-240619-143201			
Restricted © Innomotics 2024	F70+G04+H02+L22+L51			Revision AA	Creation date 2024-06-19	Language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4310B

SIMOTICS SD - 315 S - IM B3 - 4p

Special design

F70	Mounting of separately driven fan	L22	Bearing design for increased cantilever forces
G04	Mounted rotary pulse encoder LL 861 900 220	L51	Bearing insulation NDE
H02	Vibration-proof version		

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	Document type Technical data sheet			Document status Released			
	Document title 1LE5504-3AB02-2AF4-Z			Document number TDS-240619-143201			
Restricted © Innomotics 2024	F70+G04+H02+L22+L51			Revision AA	Creation date 2024-06-19	Language en	Page 2/2