

SIMOTICS SD - 315 S - IM B35 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

-/-

[illegible]

Sound level (SPL / SWL) at 50Hz 60Hz	66 / 80 dB(A) ^{2) 3)}	71 / 85 dB(A) ^{2) 3)}	Condensate drainage holes	(Standard) Yes	
Moment of inertia	2.7400 kg m²		External earthing terminal	(Standard) Yes	
Bearing DE NDE	6319 C3	6319 C3	Vibration severity grade	Grade A	
permissible lateral force on (N) (N)	X ₀ : 9300	X _{0.5} : 8650	X _{max} : 8000	Thermal class	F
bearing lifetime			Duty type	S1	
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional	
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h		Frame material	cast iron	
Lubricants	UNIREX N3		Net weight of the motor	978 kg	
Regreasing device	Flat type lubricating nipple		Coating (paint finish)	Standard paint finish C2	
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030	
Type of bearing	Locating bearing DE		Motor protection	without (Standard)	
Bearing insulation DE / Bearing insulation NDE	Yes (Non-drive end)		Method of cooling	IC411 - self ventilated, surface cooled	

Terminal box position	box at the top	Max. cross-sectional area	240 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 45 mm
Type of terminal box	TB1Q01	Cable entry	2xM63x1,5
Contact screw thread	6xM12	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE5504-3AB03-3JA4-Z						
© INNOMOTICS 2024	L51			rev.	creation date	language	Page
				953	2024-02-27	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4310B

SIMOTICS SD - 315 S - IM B35 - 4p

Special design

L51

Bearing insulation NDE

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents			
	document type datasheet				document status released			
	title 1LE5504-3AB03-3JA4-Z				document number			
© INNOMOTICS 2024	L51				rev. 953	creation date 2024-02-27	language en	Page 2/2