## **SIEMENS**

## **Data sheet**

## 1LE5504-3AB03-4AB4-Z B02+F74+H07+M11+N03+Q82+S02+Y66

SD motor type: 1CV4310B low-voltage motor, IEC squirrel-cage rotor, self-cooled, IP55 temperature class 155(F) according to 130(B) gray cast iron housing Basic Line Premium Efficiency IE4 4-pole \* size 315S 110 kW (50 Hz) standard color RAL 7030 if no order code is specified for selecting another color. The product will be delivered with either the Siemens or Innomotics product brand. 3 AC 50 Hz 400 VD/690 VY \* 3 AC 60 Hz 460 VD IM B3 3 PTC thermistors for disconnection (2 terminals) terminal box at top B02=Acceptance test certificate 3.1 according to EN 10204 F74=Sheet metal fan cover H07=Stainless screws (external) M11=Rating plate made of stainless steel N03=Temperature class 155, (F), utilized according to 155 (F), with increased coolant temperature Q82=extension of the liability for defects by 24 to a total of 36 months from delivery S02=special paint finish Y66=Non-standard colors

## Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
<a href="https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW">https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW</a>
Industry Mall (Online ordering system)
<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>

