

SD motor type: 1CV4314B low-voltage motor, IEC squirrel-cage rotor, self-cooled, IP55 temperature class 155(F) according to 130(B) gray cast iron housing Basic Line Premium Efficiency IE4 4-pole \* size 315L 160 kW (50 Hz) standard color RAL 7030 if no order code is specified for selecting another color. Purchase of this product is exclusively governed by the Innomatics T&Cs located at <https://www.innomotics.com/terms-and-conditions> 3 AC 50HZ 380VD/660VY \* 3 AC 60HZ 440VD IM V 1, flange: FF600 (A660) 3 PTC thermistors for disconnection (2 terminals) terminal box at top B02=Acceptance test certificate 3.1 according to EN 10204 D47=TR CU product safety certificate EAC for Eurasian customs union H00=Canopy H70=Second exterior grounding N31=Increased humidity/temp. with 60 to 100 g water per m3 air Q01=Measuring nipple for SPM shock pulse measurement for bearing inspection Q60=3 resistance thermometers Pt100 2-wire input (6 terminals) R62=Auxiliary terminal box cast iron (small) S03=Special paint finish, sea air resistant Y56=PAINT FINISH IN SPECIAL RAL COLOURS (SELECTION SEE CATALOG) RAL....

#### Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)

<https://support.industry.siemens.com/cs/products?mf=ps&lc=en-WW>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com>

