

Data sheet for three-phase Squirrel-Cage-Motors INNOMOTICS



Motor type : 1CV4315B INNOMOTICS SD - 315 L - IM V1 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

Electrical data

-/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	200.00	-/-	350.00	1490	1280.0	96.7	96.9	96.8	0.85	0.82	0.73	7.8	3.4	3.1	IE4
690	Y	50	200.00	-/-	205.00	1490	1280.0	96.7	96.9	96.8	0.85	0.82	0.73	7.8	3.4	3.1	IE4
460	Δ	60	200.00	-/-	305.00	1791	1070.0	96.5	96.5	96.2	0.85	0.81	0.72	9.5	3.7	3.4	IE4
460	Δ	60	230.00	-/-	345.00	1788	1230.0	96.8	97.0	96.8	0.86	0.83	0.75	8.2	3.2	3.0	IE4
IM V1 / IM3011			FS 315 L				IP55	UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 26.6 s 41.9 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	69 / 83 dB(A) ^{2) 3)}	73 / 88 dB(A) ^{2) 3)}	External earthing terminal	(Standard) Yes
Moment of inertia	4.3700 kg m ²		Vibration severity grade	Grade A
Bearing DE NDE	6319 C3	6319 C3	Thermal class	F
permissible lateral force on (N)	X ₀ : 9300	X _{0.5} : 8650	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad, min} for coupling operation 50 60Hz ¹⁾	20000 h	16000 h	Frame material	cast iron
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h		Net weight of the motor	1340 kg
Lubricants	UNIREX N3		Coating (paint finish)	Special paint finish C3
Regreasing device	Flat type lubricating nipple		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	without (Standard)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	(Standard) Yes			

Terminal box

Terminal box position	box at the top	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 45 mm
Type of terminal box	TB1Q01	Cable entry	2xM63x1,5 - 2xM20x1,5
Contact screw thread	6xM12	Cable gland	4 plugs

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
INNOMOTICS	Document type Technical data sheet			Document status Released			
	Document title 1LE5504-3AB53-4GA4-Z			Document number TDS-240819-133906			
	Restricted © Innomotics 2024			Revision AA	Creation date 2024-08-19		

INNOMOTICS SD - 315 L - IM V1 - 4p

Q01	Measuring nipple for SPM shock pulse measurement to monitor bearings	R62	Cast iron auxiliary terminal box (small)
Q02	Anti-condensation heating for 230 V (2 terminals)	S02	Special paint finish C3
Q72	2 Pt100 resistance thermometers for bearings (4 terminals)		

Space heaters

Technical data:	1-phase, 230V, 218W
-----------------	---------------------

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
INNOMOTICS	Document type Technical data sheet			Document status Released			
	Document title 1LE5504-3AB53-4GA4-Z			Document number TDS-240819-133906			
Restricted © Innomotics 2024	Q01+Q02+Q72+R62+S02			Revision AA	Creation date 2024-08-19	Language en	Page 2/2