

SD motor type: 1CV4315B low-voltage motor, IEC squirrel-cage rotor, self-cooled, IP55 temperature class 155(F) according to 130(B) gray cast iron housing Basic Line Premium Efficiency IE4 4-pole * size 315L 200 kW (50 Hz) standard color RAL 7030 if no order code is specified for selecting another color. The product will be delivered with either the Siemens or Innomotics product brand. 3 AC 50 Hz 400 VD/690 VY * 3 AC 60 Hz 460 VD IM V 1, flange: FF600 (A660) 3 resistance thermometers Pt100 2 wire circuit (6 terminals) terminal box at top B02=Acceptance test certificate 3.1 according to EN 10204 B12=Seaworthy packaging for non-overseas customers L51=Bearing insulation NDE (non drive end) M11=Rating plate made of stainless steel N06=Temperature class 155 (F), utilized according to 130(B), coolant temperature 50°, derating approx. 8% Q72=2 resistance thermometers Pt100 in basic configuration for bearing (4 terminals) R67=2 small cast iron auxiliary terminal boxes Y58=Non-standard cylindrical shaft extension, DE (DE)

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com>

