

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4310C

SIMOTICS SD - 315 S - IM B35 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data	Safe Area
	-/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL	
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N		
DOL duty (S1) - 155(F) to 130(B)																		
380	Δ	50	75.00	-/-	142.00	992	720.0	95.4	95.6	95.2	0.84	0.79	0.69	8.2	2.7	3.5	IE4	
660	Y	50	75.00	-/-	82.00	992	720.0	95.4	95.6	95.2	0.84	0.79	0.69	8.2	2.7	3.5	IE4	
440	Δ	60	75.00	-/-	124.00	1193	600.0	95.8	95.7	94.9	0.83	0.78	0.67	9.2	3.1	3.9	IE4	
440	Δ	60	90.00	-/-	145.00	1192	720.0	95.8	96.0	95.7	0.85	0.81	0.72	8.0	2.5	3.3	IE4	
IM B35 / IM2001			FS 315 S				IP55	UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 25 s 34 s									

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	63 / 77 dB(A) ^{2) 3)}	65 / 79 dB(A) ^{2) 3)}	External earthing terminal	(Standard) Yes
Moment of inertia	3.1800 kg m ²		Vibration severity grade	Grade A
Bearing DE NDE	6319 C3	6319 C3	Thermal class	F
permissible lateral force on (N)	X ₀ : 10600	X _{0.5} : 9900	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h		Net weight of the motor	886 kg
Lubricants	UNIREX N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	-/-		Color, paint shade	RAL7030
Grease nipple	-/-		Motor protection	without (Standard)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	(Standard) Yes			

Terminal box

Terminal box position	box at the top	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 45 mm
Type of terminal box	TB1Q01	Cable entry	2xM63x1,5
Contact screw thread	6xM12	Cable gland	2 plugs

Notes:		
I_L/I_N = locked rotor current / current nominal	1) L_{10mh} according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_L/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_B/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents		
IN LVM		SPC						
SIEMENS	document type	datasheet			document status			
	released							
	title	1LE5504-3AC03-3JA4-Z			document number			
© INNOMOTICS 2023	B02				rev.	creation date	language	Page
					951	2023-12-14	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4310C

SIMOTICS SD - 315 S - IM B35 - 6p

Special design

B02

Acceptance test certificate 3.1 acc. to EN 10204

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE5504-3AC03-3JA4-Z			document number			
© INNOMOTICS 2023	B02			rev. 951	creation date 2023-12-14	language en	Page 2/2