

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4316C

SIMOTICS SD - 315 L - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data	Safe Area
	-/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
380	Δ	50	160.00	-/-	310.00	993	1540.0	96.2	96.4	96.1	0.82	0.77	0.67	8.0	2.9	3.1	IE4
660	Y	50	160.00	-/-	177.00	993	1540.0	96.2	96.4	96.1	0.82	0.77	0.67	8.0	2.9	3.1	IE4
440	Δ	60	160.00	-/-	265.00	1194	1280.0	96.2	96.2	95.7	0.82	0.77	0.67	9.2	3.1	3.4	IE4
440	Δ	60	192.00	-/-	310.00	1192	1540.0	96.2	96.4	96.2	0.84	0.80	0.72	7.8	2.6	2.8	IE4
IM B3 / IM1001			FS 315 L				IP55	UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 46.2 s 69.1 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	70 / 85 dB(A) ^{2) 3)}	71 / 85 dB(A) ^{2) 3)}	External earthing terminal	(Standard) Yes
Moment of inertia	5.6700 kg m ²		Vibration severity grade	Grade A
Bearing DE NDE	6319 C3	6319 C3	Thermal class	F
permissible lateral force on (N)	X ₀ : 10600	X _{0.5} : 9900	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Relubrication interval/quantity DE NDE	40 g 40 g	6000 h	Net weight of the motor	1260 kg
Lubricants	UNIREX N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	-/-		Color, paint shade	RAL7030
Grease nipple	-/-		Motor protection	3 resistance thermometers PT100 (6 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	(Standard) Yes			

Terminal box

Terminal box position	box at the top	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38 mm - 45 mm
Type of terminal box	TB1Q01	Cable entry	2xM63x1,5 - 2xM20x1,5
Contact screw thread	6xM12	Cable gland	4 plugs

Notes:		
I_L/I_N = locked rotor current / current nominal	1) L_{10mh} according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_L/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_K/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
SIEMENS	document type			document status			
	datasheet			released			
	title			document number			
	1LE5504-3AC63-3AH4-Z						
© INNOMOTICS 2023	D22+D47+H02+Q72+R62			rev.	creation date	language	Page
				951	2023-12-14	en	1/2

SIMOTICS SD - 315 L - IM B3 - 6p

D22	Motor without CE character for export outside the EEA (see EU regulation 2019/1781)	Q72	2 Pt100 resistance thermometers for bearings (4 terminals)
D47	TR CU product safety certificate EAC for the Eurasian Customs Union	R62	Cast iron auxiliary terminal box (small)
H02	Vibration-proof version		

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE5504-3AC63-3AH4-Z						
	D22+D47+H02+Q72+R62			rev.	creation date	language	Page
© INNOMOTICS 2023				951	2023-12-14	en	2/2