

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3352C

SIMOTICS SD - 355 L - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data																		Safe Area	
																		-/-	
U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL		
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N			
DOL duty (S1) - 155(F) to 130(B)																			
400	Δ	50	315.00	-/-	580.00	993	3050.0	95.8	95.8	95.3	0.82	0.77	0.66	7.8	2.9	3.2	IE3		
690	Y	50	315.00	-/-	335.00	993	3050.0	95.8	95.8	95.3	0.82	0.77	0.66	7.8	2.9	3.2	IE3		
460	Δ	60	315.00	-/-	500.00	1194	2500.0	95.8	95.7	95.0	0.82	0.77	0.65	9.2	3.2	3.6	IE3		
460	Δ	60	380.00	-/-	590.00	1192	3050.0	95.8	95.9	95.5	0.84	0.80	0.70	8.2	2.6	3.0	IE3		
IM B3 / IM1001			FS 355 L				IP55	UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m										Locked rotor time (hot / cold) : 35.3 s 54.7 s									

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	75 / 90 dB(A) ^{2) 3)}	78 / 94 dB(A) ^{2) 3)}	Condensate drainage holes	(Standard) Yes
Moment of inertia	11.6000 kg m ²		External earthing terminal	(Standard) Yes
Bearing DE NDE	6320 C4	6320 C4	Vibration severity grade	Grade A
permissible lateral force on (N) (N)	X ₀ : 11200	X _{0.5} : 10500	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	60 g 60 g	6000 h	Frame material	cast iron
Lubricants	UNIREX N3		Net weight of the motor	2040 kg
Regreasing device	-/-		Coating (paint finish)	Special paint finish C3
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing DE		Motor protection	3 PTC thermistors - for tripping (2 terminals)
Bearing insulation DE / Bearing insulation NDE	Yes (Non-drive end)		Method of cooling	IC416 - separately ventilated, surface cooled

Terminal box

Terminal box position	at the right	Max. cross-sectional area	300 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	63 mm - 70 mm
Type of terminal box	TB3R01	Cable entry	2xM80x2 - 2xM20x1,5
Contact screw thread	6xM16	Cable gland	-/-

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque
1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents		
	document type datasheet				document status released			
	title 1LE5603-3BC23-4AB5-Z				document number			
© INNOMOTICS 2023	F70+G11+L51				rev. 951	creation date 2023-12-14	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3352C

SIMOTICS SD - 355 L - IM B3 - 6p

Special design

F70	Mounting of separately driven fan	L51	Bearing insulation NDE
G11	Rotary pulse encoder Sendix 5020 (HTL)		

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE5603-3BC23-4AB5-Z			document number			
© INNOMOTICS 2023	F70+G11+L51			rev. 951	creation date 2023-12-14	language en	Page 2/2