

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3352D SIMOTICS SD - 355 L - IM B3 - 8p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data																	Safe Area	
																	-/-	
U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL	
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N		
DOL duty (S1) - 155(F) to 130(B)																		
400	Δ	50	315.00	-/-	600.00	744	4050.0	94.6	94.9	94.6	0.80	0.75	0.64	7.3	2.5	3.0	IE3	
690	Y	50	315.00	-/-	350.00	744	4050.0	94.6	94.9	94.6	0.80	0.75	0.64	7.3	2.5	3.0	IE3	
460	Δ	60	315.00	-/-	530.00	895	3350.0	95.0	95.1	94.6	0.78	0.72	0.60	8.6	2.7	3.2	IE3	
460	Δ	60	380.00	-/-	620.00	893	4050.0	95.0	95.3	95.1	0.81	0.77	0.67	7.7	2.3	2.6	IE3	
IM B3 / IM1001			FS 355 L				IP55	UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m										Locked rotor time (hot / cold) : 24.3 s 42.3 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	73 / 88 dB(A) ^{2) 3)}	78 / 93 dB(A) ^{2) 3)}	External earthing terminal	(Standard) Yes
Moment of inertia	14.0000 kg m ²		Vibration severity grade	Grade A
Bearing DE NDE	NU 320	6320 C4	Thermal class	F
permissible lateral force on (N) (N)	X ₀ : 44600	X _{0.5} : 25000	X _{max} : 16000	Duty type S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Relubrication interval/quantity DE NDE	60 g 60 g	6000 h	Net weight of the motor	2310 kg
Lubricants	UNIREX N3		Coating (paint finish)	Special paint finish C3
Regreasing device	-/-		Color, paint shade	RAL7030
Grease nipple	-/-		Motor protection	3 PTC thermistors - for tripping (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	(Standard) Yes			

Terminal box

Terminal box position	box at the top, socket left	Max. cross-sectional area	300 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	63 mm - 70 mm
Type of terminal box	TB3R01	Cable entry	2xM80x2 - 2xM20x1,5
Contact screw thread	6xM16	Cable gland	-/-

Notes:		
I_A/I_N = locked rotor current / current nominal	1) L_{10mh} according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_A/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_B/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
SIEMENS	document type			document status			
	datasheet			released			
	title			document number			
	1LE5603-3BD23-4AB0-Z						
© INNOMOTICS 2023	L22			rev.	creation date	language	Page
				951	2023-12-14	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3352D

SIMOTICS SD - 355 L - IM B3 - 8p

Special design

L22 Bearing design for increased cantilever forces

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE5603-3BD23-4AB0-Z			document number			
© INNOMOTICS 2023	L22			rev. 951	creation date 2023-12-14	language en	Page 2/2