

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4352C

SIMOTICS SD - 355 L - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Safe Area																		
Electrical data																		
U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL	
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N		
DOL duty (S1) - 155(F) to 130(B)																		
400	Δ	50	315.00	-/-	560.00	993	3050.0	96.6	96.8	96.5	0.84	0.80	0.71	7.8	2.8	3.2	IE4	
690	Y	50	315.00	-/-	325.00	993	3050.0	96.6	96.8	96.5	0.84	0.80	0.71	7.8	2.8	3.2	IE4	
460	Δ	60	315.00	-/-	490.00	1194	2500.0	96.5	96.5	96.1	0.84	0.80	0.70	9.2	3.2	3.5	IE4	
460	Δ	60	380.00	-/-	570.00	1192	3050.0	96.5	96.7	96.5	0.86	0.83	0.75	7.9	2.6	2.9	IE4	
IM B3 / IM1001			FS 355 L				IP55	UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 37.8 s 58.7 s									

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	73 / 89 dB(A) ^{2) 3)}	77 / 92 dB(A) ^{2) 3)}	External earthing terminal	(Standard) Yes
Moment of inertia	12.3000 kg m ²		Vibration severity grade	Grade A
Bearing DE NDE	6320 C4	6320 C4	Thermal class	F
permissible lateral force on (N) (N)	X ₀ : 11200	X _{0.5} : N/A	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Relubrication interval/quantity DE NDE	60 g 60 g 6000 h		Net weight of the motor	2040 kg
Lubricants	UNIREX N3		Coating (paint finish)	Special paint finish C3
Regreasing device	(Standard) Flat type lubricating nipple acc. DIN 3404		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	3 PTC thermistors - for tripping (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	(Standard) Yes			

Terminal box

Terminal box position	box at the angle 45°, socket right	Max. cross-sectional area	300 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	63 mm - 70 mm
Type of terminal box	TB3R01	Cable entry	2xM80x2 - 2xM20x1,5
Contact screw thread	6xM16	Cable gland	-/-

Notes:		
I_A/I_N = locked rotor current / current nominal	1) L_{10mh} according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_A/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_B/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
IN LVM		SPC			
SIEMENS	document type				document status
	datasheet				released
	title				document number
	1LE5604-3BC23-4AB3				
© INNOMOTICS 2023			rev.	creation date	language
			951	2023-12-14	en
				Page	1/1