

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3354B

SIMOTICS SD Pro - 355 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Safe Area																	
Electrical data								-/-									
U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 155(F)																	
400	Δ	50	400.00	-/-	690.00	1490	2550.0	96.0	96.2	95.9	0.87	0.84	0.77	7.7	2.5	2.9	IE3
690	Y	50	400.00	-/-	400.00	1490	2550.0	96.0	96.2	95.9	0.87	0.84	0.77	7.7	2.5	2.9	IE3
460	Δ	60	400.00	-/-	600.00	1792	2150.0	96.2	96.1	95.6	0.87	0.84	0.76	9.0	2.9	3.2	IE3
460	Δ	60	460.00	-/-	680.00	1790	2450.0	96.2	96.3	95.9	0.88	0.86	0.79	7.9	2.5	2.8	IE3
460	Δ	60		500	570.00	1793	2000.0	96.2	96.1	95.4	0.87	0.84	0.76	9.5	3.1	3.4	MG1
IM B3 / IM1001			FS 355 L				IP55	UKCA		IEC/EN 60034		IEC, EN, UL, CSA, NEMA MG1-12					
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 21.6 s 46.3 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	80 / 95 dB(A) ^{2) 3)}	84 / 99 dB(A) ^{2) 3)}	Condensate drainage holes	(Standard) Yes
Moment of inertia	7.0600 kg m ²		External earthing terminal	(Standard) Yes
Bearing DE NDE	6320 C4	6320 C4	Vibration severity grade	Grade A
permissible lateral force on (N) (N)	X ₀ : 9900	X _{0.5} : 9300	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	60 g 60 g	6000 h	Frame material	cast iron
Lubricants	UNIREX N3		Net weight of the motor	2080 kg
Regreasing device	-/-		Coating (paint finish)	Special paint finish C3
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing DE		Motor protection	1 temperature sensor KTY84-130 (2 terminals)
Bearing insulation DE / Bearing insulation NDE	Yes (Non-drive end)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	box at the angle 45°, socket left	Max. cross-sectional area	300 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	63 mm - 70 mm
Type of terminal box	TB3R01	Cable entry	2xM80x2 - 2xM20x1,5
Contact screw thread	6xM16	Cable gland	-/-

Notes:		
I_A/I_N = locked rotor current / current nominal	1) L_{10mh} according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_A/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_B/M_N = break down torque / nominal torque		

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents 		
	document type datasheet				document status released			
	title 1LE5683-3BB43-4AF2-Z				document number			
© INNOMOTICS 2023	L51+Q01				rev. 951	creation date 2023-12-14	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3354B

SIMOTICS SD Pro - 355 L - IM B3 - 4p

Special design

L51

Bearing insulation NDE

Q01

Measuring nipple for SPM shock pulse measurement to monitor bearings

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents	
	document type datasheet				document status released	
	title 1LE5683-3BB43-4AF2-Z				document number	
© INNOMOTICS 2023	L51+Q01				rev. 951	creation date 2023-12-14
						language en