

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3355B

SIMOTICS SD Pro - 355 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Safe Area																	
Electrical data								-/-									
U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 155(F)																	
400	Δ	50	500.00	-/-	880.00	1491	3200.0	96.0	96.1	95.8	0.85	0.81	0.72	8.2	2.9	3.2	IE3
690	Y	50	500.00	-/-	510.00	1491	3200.0	96.0	96.1	95.8	0.85	0.81	0.72	8.2	2.9	3.2	IE3
460	Δ	60	500.00	-/-	770.00	1792	2650.0	96.2	96.1	95.5	0.85	0.81	0.71	9.5	3.3	3.6	IE3
460	Δ	60	580.00	-/-	880.00	1790	3100.0	96.2	96.3	95.9	0.86	0.83	0.75	8.3	2.9	3.1	IE3
460	Δ	60		600	710.00	1793	2400.0	96.2	96.0	95.3	0.85	0.81	0.71	10.0	3.7	4.0	MG1
IM B3 / IM1001			FS 355 L			IP55	UKCA	IEC/EN 60034		IEC, EN, UL, CSA, NEMA MG1-12							
Environmental conditions : -20 °C - +40 °C / 1,000 m										Locked rotor time (hot / cold) : 14.5 s 37.7 s							

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	81 / 96 dB(A) ^{2) 3)}	84 / 99 dB(A) ^{2) 3)}	Condensate drainage holes	(Standard) Yes
Moment of inertia	8.3600 kg m ²		External earthing terminal	(Standard) Yes
Bearing DE NDE	6320 C4	6320 C4	Vibration severity grade	Grade A
permissible lateral force on (N) (N)	X ₀ : 9900	X _{0.5} : 9300	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	60 g 60 g	6000 h	Frame material	cast iron
Lubricants	UNIREX N3		Net weight of the motor	2310 kg
Regreasing device	-/-		Coating (paint finish)	Special paint finish C3
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing DE		Motor protection	3 PTC thermistors - for tripping (2 terminals)
Bearing insulation DE / Bearing insulation NDE	Yes (Non-drive end)		Method of cooling	IC416 - separately ventilated, surface cooled

Terminal box

Terminal box position	box at the top, socket left	Max. cross-sectional area	300 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	63 mm - 70 mm
Type of terminal box	TB3R01	Cable entry	4xM80x2 - 2xM20x1,5
Contact screw thread	12xM16	Cable gland	-/-

Notes:

I _A /I _N = locked rotor current / current nominal	1) L _{10mh} according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _A /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _K /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents		
IN LVM		SPC						
SIEMENS	document type	datasheet			document status			
					released			
	title	1LE5683-3BB53-4AB0-Z			document number			
© INNOMOTICS 2023	F70+G04+L51+Q02				rev.	creation date	language	Page
					951	2023-12-14	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3355B

SIMOTICS SD Pro - 355 L - IM B3 - 4p

Special design

F70	Mounting of separately driven fan	L51	Bearing insulation NDE
G04	Mounted rotary pulse encoder LL 861 900 220	Q02	Anti-condensation heating for 230 V (2 terminals)

Additional information:

Space heaters

Technical data: 1-phase, 230V, 218W

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents 	
	document type datasheet			document status released			
	title 1LE5683-3BB53-4AB0-Z			document number			
© INNOMOTICS 2023	F70+G04+L51+Q02			rev. 951	creation date 2023-12-14	language en	Page 2/2