

Data sheet for three-phase Squirrel-Cage-Motors

MLFB-Ordering data : 1LG4207-4AA60

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Electrical data :							
Rated voltage :		(6) 400 VD/690 VY, 50 Hz, 460 VD, 60 Hz					
Frequency :		50 Hz			60 Hz		
Rated power :		30.00 kW			34.50 kW /		
Rated speed :		1465 1/min			1765 1/min		
Rated torque :		195.6 Nm			186.7 Nm		
Rated current (IE) :		VD	VY		VD	VY	
		56.0 A	32.5 A		54.0 A		
Starting / rated current :		6.7			6.8		
Breakdown / rated torque :		3.4			3.4		
Starting / rated torque :		2.5			2.5		
		4/4	3/4	2/4	4/4	3/4	2/4
Efficiency %		90.7 %	91.1 %	90.6 %	92.4 %	92.6 %	91.9 %
Power factor :		0.85	0.80	0.70	0.86	0.86	0.73
Efficiency class :		IE1			IE1		
no value							
No							

Mechanical data :		
Sound pressure level 50Hz/60Hz (load) :		
66.0(A)		70.0(A)
Moment of inertia :		
0.19 kg m ²		
Bearing DE :		
6212 ZC3		
Bearing NDE :		
6212 ZC3		
Type of bearing :		
Locating bearing NDE (standard)		
Condensate drainage holes :		
Yes		
Regreasing device :		
No		
Lubricants :		
Esso Unirex N3		
Grease lifetime/Relubrication interval :		
40000 h		
Quantity of grease for relubrication :		
null g		
External earthing terminal :		
Yes		
Coating :		

Explosion protection :	
Type of protection :	without (standard)

Environmental conditions :	
Ambient temperature :	-20.0 °C - +40 °C
Altitude above sea level :	1000 m
Standards and specifications :	IEC, DIN, ISO, VDE, EN

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

General data :	
Frame size :	200 L
Design of electrical machine :	(0) IM B3 / B6 / B7 / B8 / V5 without canopy
Weight in kg, without optional accessories :	205.00 kg
Frame material :	Cast iron
Degree of protection :	IP 55
Method of cooling, TEFC :	IC 411
Vibration class :	A
Insulation :	155(F) to 130(B)
Duty type :	S1 - continuous duty
Direction of rotation :	Bi-directional

Terminal box :	
Material of terminal box :	Aluminum
Type of terminal box :	gk 430
Contact screw thread :	M6
Max. cross-sectional area :	25.00 mm ²
Cable diameter from ... to ... :	27.0mm - 35.0mm
Cable entry :	2xM50x1,5
Cable gland null	2 plugs

Special design :	
------------------	--