

Data sheet for three-phase Squirrel-Cage-Motors

MLFB-Ordering data : **1LG6207-4PM30-Z**
D47+K10

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Electrical data :

Rated voltage : (3) 500 VY, 50 Hz

Frequency :	50 Hz
Rated power :	30.00 kW
Rated speed :	1470 1/min
Rated torque :	194.9 Nm
Rated current (EFF) :	VY 44.0 A
Starting / rated current :	6.7
Breakdown / rated torque :	3.3
Starting / rated torque :	2.6
Efficiency %	4/4 91.7 % 3/4 91.8 % 2/4 91.2 %
Power factor :	0.85 0.80 0.70
Efficiency class :	-

Mechanical data :

Sound pressure level 50Hz/60Hz (load) :	62.0(A)
Moment of inertia :	0.2344 kg m²
Bearing DE :	6212 ZC3
Bearing NDE :	6212 ZC3
Type of bearing :	Locating bearing NDE (standard)
Condensate drainage holes :	Yes
Regreasing device :	No
Lubricants :	Esso Unirex N3
Grease lifetime/Relubrication interval :	40000 h
Quantity of grease for relubrication :	null g
External earthing terminal :	Yes
Coating :	

Explosion protection :

Type of protection : without (standard)

Environmental conditions :

Ambient temperature :	-20.0 °C - +40 °C
Altitude above sea level :	1000 m
Standards and specifications :	IEC, DIN, ISO, VDE, EN

General data :

Frame size :	200 L
Design of electrical machine :	(0) IM B3 / B6 / B7 / B8 / V5 without canopy
Weight in kg, without optional accessories :	225.00 kg
Frame material :	Cast iron
Degree of protection :	IP 55
Method of cooling, TEFC :	IC 411
Vibration class :	A
Insulation :	155(F) to 155(F)
Duty type :	inverter duty only
Direction of rotation :	Bi-directional

Terminal box :

Material of terminal box :	Aluminum
Type of terminal box :	gk 430
Contact screw thread :	M6
Max. cross-sectional area :	25.00 mm²
Cable diameter from ... to ... :	27.0mm - 35.0mm
Cable entry :	2xM50x1,5
Cable gland null	2 plugs

Special design :

K10 Terminal box mounted on the left side