

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2073D

SIMOTICS XP - 71 M - IM B3 - 8p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

II 3D Ex tc IIIB T 120°C Dc

-/-

Electrical data

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			cosφ ³⁾			I _A /I _N I _I /I _N	M _A /M _N T _I /T _N	M _K /M _N T _B /T _N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	0.12	-/-	0.66	640	1.8	39.8	39.3	34.5	0.66	0.55	0.44	1.8	1.8	1.8	IE2
690	Y	50	0.12	-/-	0.38	640	1.8	39.8	39.3	34.5	0.66	0.55	0.44	1.8	1.8	1.8	IE2
460	Δ	60	0.14	-/-	0.69	795	1.7	40.0	39.0	34.6	0.64	0.54	0.43	2.1	1.9	2.0	IE2
460	Δ	60	0.12	-/-	0.66	815	1.4	40.0	38.0	33.0	0.57	0.49	0.39	2.1	2.3	2.4	IE2
IM B3 / IM 1001		FS 71 M		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN									

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 108.7 s | 138.8 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	48 / 59 dB(A) ^{2) 3)}	52 / 63 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0010 kg m ²		Thermal class	F
Bearing DE NDE	6202 2Z C3	6202 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} , F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	7 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 B00	Cable entry	1xM25x1,5
Contact screw thread	M4		

Notes:

I_A/I_N = locked rotor current / current nominal
 M_K/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque
 1) L_{10mh} according to DIN ISO 281 10/2010
 2) at rated power / at full load
 3) Value is valid only for DOL operation with motor design IC411

responsible dep. IN LVM	technical reference	created by SPC	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
	document type datasheet	document status released			document number
	title 1MB1021-0CD33-4AA4	rev. 951	creation date 2023-12-14		
© INNOMOTICS 2023					