

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3164B SIMOTICS XP - 160 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

II 3G Ex ec IIC T3 Gc																	
-/-																	
U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
415	Δ	50	13.05	-/-	24.50	1465	85.1	92.4	92.4	91.3	0.80	0.74	0.61	9.1	3.2	3.9	IE3
480	Δ	60	15.05	-/-	24.00	1765	81.4	92.5	92.3	91.5	0.81	0.75	0.64	9.1	3.1	3.8	IE2
480	Δ	60	15.00	-/-	24.00	1775	81.0	93.0	92.9	92.1	0.81	0.75	0.64	8.9	3.1	3.8	IE3
IM B3 / IM 1001		FS 160 L		IP56		IEC/EN 60034		IEC, DIN, ISO, VDE, EN									
Environmental conditions : -20 °C - +55 °C / 1,000 m									Locked rotor time (hot / cold) : 24.6 s 33.3 s								
These values are calculated. The final rating plate data will be calculated when the order is placed																	
The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.																	

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	58 / 66 dB(A) ^{2) 3)}	66 / 74 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0890 kg m ²		Thermal class	F
Bearing DE NDE	6209 2Z C3	6209 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	106 kg
Grease nipple	-/-		Coating (paint finish)	Special paint finish, resistant to salt-laden air C4
Type of bearing	Locating bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5-2xM16x1,5
Contact screw thread	M5		

Notes:		
I_A/I_N = locked rotor current / current nominal	1) L_{10mh} according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_A/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_K/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
SIEMENS	document type			document status			
	datasheet			released			
	title			document number			
	1MB1033-1DB43-5AB4-Z						
© INNOMOTICS 2023	H07+H22+L20+N07+503			rev.	creation date	language	Page
				951	2023-12-14	en	1/2

SIMOTICS XP - 160 L - IM B3 - 4p

H07	Stainless steel screws and bolts (outside the motor)	N07	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 55°C, power reduced
H22	IP 56 degree of protection	S03	Special paint finish in sea air resistant C4
L20	Locating bearing, DE		

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents		
	document type datasheet				document status released			
	title 1MB1033-1DB43-5AB4-Z				document number			
© INNOMOTICS 2023	H07+H22+L20+N07+S03				rev. 951	creation date 2023-12-14	language en	Page 2/2