

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2184C SIMOTICS XP - 180 L - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data II 3D Ex tc IIIB T 120°C Dc -/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	15.00	-/-	31.00	975	147.0	89.7	90.1	89.5	0.78	0.71	0.59	6.0	2.5	3.1	IE2
690	Y	50	15.00	-/-	17.90	975	147.0	89.7	90.1	89.5	0.78	0.71	0.59	6.0	2.5	3.1	IE2
460	Δ	60	18.00	-/-	31.00	1170	147.0	91.7	92.2	91.8	0.80	0.74	0.64	6.0	2.4	2.9	IE2
460	Δ	60	15.00	-/-	27.00	1178	122.0	90.2	90.2	89.0	0.77	0.70	0.58	6.9	2.8	3.4	IE2
IM B3 / IM 1001		FS 180 L				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 24.7 s 41.2 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	57 / 70 dB(A) ^{2) 3)}	60 / 73 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.1700 kg m ²		Thermal class	F
Bearing DE NDE	6210 2Z C3	6210 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	155 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5-2xM16x1,5
Contact screw thread	M5		

Notes: I_A/I_N = locked rotor current / current nominal 1) L_{10mh} according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411
M_K/M_N = locked rotor torque / torque nominal 2) at rated power / at full load
M_K/M_N = break down torque / nominal torque

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
IN LVM		SPC			
	document type				document status
	datasheet				released
	title				document number
	1MB1521-1EC43-4AB4				
© INNOMOTICS 2023		rev.	creation date	language	Page
		951	2023-12-14	en	1/1

