

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3204A SIMOTICS XP - 200 L - IM V1 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data II 3D Ex tc IIIB T 120°C Dc -/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	30.00	-/-	53.00	2955	97.0	93.3	93.6	93.3	0.87	0.83	0.75	7.0	2.5	3.3	IE3
690	Y	50	30.00	-/-	31.00	2955	97.0	93.3	93.6	93.3	0.87	0.83	0.75	7.0	2.5	3.3	IE3
460	Δ	60	33.50	-/-	52.00	3555	90.0	93.0	93.1	92.6	0.87	0.84	0.77	7.1	2.5	3.3	IE3
460	Δ	60	30.00	-/-	47.00	3560	80.0	92.4	92.2	91.4	0.87	0.83	0.74	7.6	2.9	3.6	IE3
IM V1 / IM 3011		FS 200 L				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 34.3 s 52.7 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	73 / 80 dB(A) ^{2) 3)}	78 / 86 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.1340 kg m ²		Thermal class	F
Bearing DE NDE	6212 2Z C3	6212 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	20000 h	16000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	225 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	35 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M6		

Notes: I_A/I_N = locked rotor current / current nominal 1) L_{10mh} according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411
M_K/M_N = locked rotor torque / torque nominal 2) at rated power / at full load
M_K/M_N = break down torque / nominal torque

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents 		
	document type datasheet				document status released			
	title 1MB1523-2AA43-4GB4-Z				document number			
© INNOMOTICS 2023	H00				rev. 951	creation date 2023-12-14	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3204A

SIMOTICS XP - 200 L - IM V1 - 2p

Special design

H00 Canopy

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1MB1523-2AA43-4GB4-Z				document number
© INNOMOTICS 2023	H00	rev. 951	creation date 2023-12-14	language en	Page 2/2

