

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3282B

SIMOTICS XP - 280 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data II 3D Ex tc IIIB T 120°C Dc -/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	90.00	-/-	157.00	1485	580.0	95.2	95.5	95.3	0.87	0.84	0.76	7.2	2.6	3.0	IE3
690	Y	50	90.00	-/-	91.00	1485	580.0	95.2	95.5	95.3	0.87	0.84	0.76	7.2	2.6	3.0	IE3
460	Δ	60	104.00	-/-	158.00	1785	560.0	95.0	95.3	94.9	0.87	0.85	0.77	7.0	2.6	2.9	IE2
460	Δ	60	90.00	-/-	136.00	1788	480.0	95.4	95.5	94.9	0.87	0.84	0.75	8.0	2.9	3.3	IE3
IM B3 / IM 1001		FS 280 M				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					Grade 3	
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 28.6 s 46.3 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	70 / 84 dB(A) ^{2) 3)}	79 / 93 dB(A) ^{2) 3)}	External earthing terminal	With (standard)
Moment of inertia	1.7000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6317 C3	6317 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} ¹⁾ for coupling operation 50 60Hz	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	30 g 30 g 8000 h		Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	670 kg
Regreasing device	With (standard)		Coating (paint finish)	Standard paint finish C2
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	120 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 45 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10		

Notes: I_A/I_N = locked rotor current / current nominal 1) L_{10mh} according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411
M_K/M_N = locked rotor torque / torque nominal 2) at rated power / at full load
M_B/M_N = break down torque / nominal torque

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents 		
	document type datasheet				document status released			
	title 1MB1523-2DB23-4AB4-Z				document number			
© INNOMOTICS 2023	D32+D34				rev. 951	creation date 2023-12-14	language en	Page 1/2

SIMOTICS XP - 280 M - IM B3 - 4p

Special design

D32	Ex certification for China	D34	China Energy Efficiency Label
-----	----------------------------	-----	-------------------------------

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type			document status			
	datasheet			released			
	title			document number			
	1MB1523-2DB23-4AB4-Z						
	D32+D34			rev.	creation date	language	Page
© INNOMOTICS 2023				951	2023-12-14	en	2/2